



03 CO
SAD
#5

Attorney Docket No. 0275S-000336

3-21-01

Group Art Unit: ~~not assigned~~
MOORE
Examiner: ~~not assigned~~
Applicant: Cockburn et al
Serial No.: 09/616,765
Filed: July 14, 2000
For: DUAL FILTER VACUUM CLEANER
APPARATUS

**TRANSMITTAL OF
PRIORITY DOCUMENT**

Hon. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231 on Sept. 22, 2000.

By

Sir:

Pursuant to the provisions of 35 U.S.C. 119, enclosed herewith is a certified copy of United Kingdom Application No. 991 6759.5, filed July 17, 1999 as identified in the Declaration

of this application. In support of applicant's priority claim, please enter this document into the file.

Respectfully submitted,

HARNESS, DICKEY & PIERCE, P.L.C.
Attorney For Applicant



Mark D. Elchuk
Reg. No. 33,686

P.O. Box 828
Bloomfield Hills, MI 48303
(248) 641-1600
MDE/jo
September 22, 2000



INVESTOR IN PEOPLE

**The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ**

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated

17 July 2000

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH**Request for grant of a patent***(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)***1. Your reference**

P-UK-HW1011#SP

2. Patent application number
*(The Patent Office will fill in this part)***9916759.5**L99 E462772-1 000223
7700 0.00 - 9916759.5**3. Full name, address and postcode of the or of each applicant** *(underline all surnames)*Black & Decker Inc.
Drummond Plaza Office Park
1423 Kirkwood Highway
Newark, Delaware
USAPatents ADP number *(if you know it)*

If the applicant is a corporate body, give the country/state of its incorporation

4187076001
Delaware, USA**4. Title of the invention**

IMPROVEMENTS IN VACUUM CLEANERS

5. Name of your agent *(if you have one)*

SG Harries, AC Dlugosz, DM Shaya, I Bell

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*Black & Decker
European Patent Department
210 Bath Road
Slough
Berks SL1 3YD
United KingdomPatents ADP number *(if you know it)*

75527/4001

THE PATENT OFFICE

17 JUL 1999

RECEIVED BY POST

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* **the or each application number**

Country

Priority application number
*(if you know it)*Date of filing
*(day / month / year)***7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application**

Number of earlier application

Date of filing
*(day / month / year)***8. Is a statement of inventorship and of right to grant of a patent required in support of this request?** *(Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))*

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	19
Claim(s)	9
Abstract	1
Drawing(s)	5 + 5



10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11.

I/We request the grant of a patent on the basis of this application

Signature

Date: 16 July 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

SIMON HARRIES 01753 500548

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Improvements in Vacuum Cleaners

The present invention relates to improvements in the filter arrangements used in vacuum cleaners and in particular to improvements in the filter arrangements used in
5 hand held battery operated vacuum cleaners.

In many known vacuum cleaners a motor powered either by a mains electricity supply or a battery pack, which may be rechargeable, rotatingly drives a fan. The fan generates an airflow within which particles of dust and debris to be collected by the
10 vacuum cleaner become entrained. The airflow generally enters the vacuum cleaner via an inlet nozzle and passes through a filter so that particles of dust and debris entrained in the airflow are removed from the airflow by the filter and are collected in a collecting chamber. A problem with this type of vacuum cleaner is that after some use the pores of the filter can become blocked by particles of dust and debris which
15 tend to bind together to form relatively large conglomerations. Once the filter becomes blocked the airflow through it is reduced and the suction power of the vacuum cleaner is reduced.

In its simplest form the filter can be a piece of woven polyester material supported in
20 a frame and located between a collecting chamber and the fan. Such a simple filter will filter out the majority of particles of dust and debris from the airflow drawn into the fan some of which particles then drop into the collecting chamber. However, such simple filters do tend to become blocked relatively quickly and can be ineffective to filter out smaller particles of dust and debris from the airflow.

25

Improved filters are known in which the filter comprises a concertina of filter material, in order to increase the surface area of the filter whilst not taking up too much space within the vacuum cleaner. However, these can also become blocked through use and the folds in the concertina of filter material provide crevices in which
30 conglomerations of particles of dust and debris can accumulate. In such filters the filter material has to be made of materials which maintain their shape once folded,

which can increase the expense of the filter material used, particularly if a fine filter is required.

It is important that the filter arrangement used in the vacuum cleaner is effectively
5 sealed within the housing of the vacuum cleaner so that none of the airflow within
which dust and debris is entrained leaks around the sides of the filter. It is desirable
that all the airflow through the fan passes through the filter so that all the particles of
dust and debris entrained in the airflow are filtered out and collected in a collecting
chamber. Such a seal for a filter will have to be effective throughout the lifetime of
10 the vacuum cleaner and may have to withstand regular disassembly of the parts of the
vacuum cleaner surrounding it in order that the collecting chamber can be emptied
and possibly so that the filter itself can be cleaned.

In some vacuum cleaners the filter is regularly removed from the housing of the
15 vacuum cleaner so that it can be cleaned. In such vacuum cleaners it is desirable to be
able to remove and replace the filter easily and without reducing the strength of any
seal between the filter and components of the vacuum cleaner surrounding it.

A first aspect of the present invention seeks to overcome some of the problems
20 discussed above by providing a filter arrangement for a vacuum cleaner which is less
vulnerable to blocking by particles of dust and debris. A second aspect of the present
invention seeks to overcome some of the disadvantages discussed above by providing
a high surface area and low volume filter in which relatively inexpensive flexible fine
filter material can be used. A third aspect of the present invention seeks to overcome
25 some of the problems discussed above by providing a filter arrangement with
improved sealing to adjacent components. A fourth aspect of the present invention
seeks to overcome some of the disadvantages discussed above by providing a
releasable fixing arrangement for a filter arrangement within a vacuum cleaner which
is easy to operate and maintains a good seal around the filter arrangement when the
30 arrangement is fixed within the vacuum cleaner.

According to a first aspect of the present invention there is provided a dual filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner, comprising a coarse pre-filter and a fine primary filter which is located rearwardly of the pre-filter in the direction of flow of the airflow.

Clearly, the pre-filter will prevent a proportion of the particles of dust and debris entrained in the airflow from reaching the primary filter and thus will reduce the blocking of the primary filter. Furthermore, the use of a coarse pre-filter means that the size of particle reaching the primary filter will be of more uniform diameter than if the pre-filter was not present, because all particles reaching the primary filter will have diameters less than the diameter of the pores in the pre-filter. It has been found that particulate material of more uniform diameter is more resistant to binding than particulate material of greatly varying diameter. This further reduces the tendency of the primary filter to become blocked because the particulate matter incident on it is less inclined to bind together to form the conglomerated masses of dust and debris particles which are responsible for the blocking up of the filter. In this way the majority of particles of dust or debris incident on the primary filter will fall away from the surface thereof and can be collected.

20

Preferably, the diameter of the pores of the pre-filter is set at a substantially uniform value, preferably at a value within the range 0.75mm to 1.75mm, and in particular a value of 1mm. It would generally be expected that using such large diameter pores would not deflect particulate matter of smaller size, such as average sized dust particles from the airflow. However, the pre-filter with an array of substantially uniform diameter pores with a diameter set at a value within this preferred range serves to deflect a significant amount of particles of dust and debris picked up in a standard manner by a vacuum cleaner and entrained in an airflow passing through it irrespective of the particle size. When the particles entrained in the airflow hit the pre-filter, their momentum is reduced or eliminated and the airflow is often insufficiently strong to recapture such particles which then fall out of the airflow and

30.

can be collected. This significantly reduces the volume of particulate material which reaches the primary filter and so will reduce blocking of the primary filter further.

It is preferred that the primary filter comprises a concertina shaped arrangement of a fine filter material in order to provide a high surface area and low volume primary filter. It is preferred that the primary filter comprises a frame comprising two opposing arrays of arms and the concertina shaped arrangement of fine filter material is supported between opposing pairs of said arms. This support for the fine filter material enables more inexpensive and flexible fine filter material to be used because the filter material is supported in the concertina formation and so does not have to maintain this formation due to its own rigidity. In a preferred arrangement said opposing arrays of arms are each arranged to form a corrugated or zig-zag formation and so are conveniently positioned to support the entire length of the opposing sides of a strip of filter material folded into a concertina formation. To further increase the surface area of the primary filter without increasing its volume it is preferred that additional pieces of fine filter material are located between adjacent arms of the arrays of arms. To ease manufacture it is preferred that the frame of the primary filter comprises a moulded plastics material.

In order to reduce the volume taken up by the dual filter arrangement without decreasing its performance it is preferred that the pre-filter is formed with a recess within which the primary filter is received.

In a preferred embodiment the pre-filter comprises an open box shaped structure in which the array of pores is located in at least one of the sides of the structure and more preferably the array of pores is located in all five sides of the structure.

The pre-filter may conveniently be made from a moulded plastics material. Preferably, such plastics material will comprise a low friction material, such as polypropylene, and may be an anti-static compound such as achieved by mixing carbon with polypropylene.

In order to provide a seal between the pre-filter and co-operating parts of the vacuum cleaner housing to ensure that all of the airflow within which dust and debris is entrained passes through the dual filter arrangement, it is preferred that the pre-filter has a peripheral rim via which it is coupled to the primary filter and/or to a housing part of a vacuum cleaner, wherein a peripheral seal element made of a resilient material surrounds said rim.

It is preferred that said seal element comprises a first rearwardly extending resilient portion which extends around the periphery of the rim of the pre-filter towards the primary filter and which surrounds the periphery of the primary filter when the dual filter arrangement is fitted to a vacuum cleaner. This helps to provide a closure between the peripheries of the pre-filter and the primary filter which is preferably sealed by ensuring that the first rearwardly extending resilient portion extends rearwardly beyond the primary filter to engage a first housing part of a vacuum cleaner to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner. This also provides a seal between the dual filter arrangement and the first housing part.

It is further preferred that the seal element comprises a second rearwardly extending resilient portion which extends around the periphery of the rim of the pre-filter towards the primary filter to engage a peripheral rim of the primary filter to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner. This provides further sealing between the pre-filter and the primary filter to prevent dust laden airflow leaking therebetween.

25

In a preferred embodiment the seal element may comprise a substantially radially outwardly extending resilient portion which extends around the periphery of the rim of the pre-filter to engage a second housing part of a vacuum cleaner to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner. Preferably, a radially inwardly extending wall is provided on the second housing part of the vacuum cleaner and a front facing surface of the radially outwardly extending resilient portion engages a rearwardly facing surface of said wall to form a seal therebetween.

It is further preferred that in use of the vacuum cleaner the seal between the radially outwardly extending resilient portion and the radially inwardly extending wall is reinforced by a pressure differential generated by an underpressure located in front of the dual filter arrangement.

5

Alternatively, the sealing element may comprise a substantially radially outwardly extending resilient portion which extends around the periphery of the rim of the pre-filter wherein the periphery of the radially outwardly extending resilient portion is arranged such that it does not engage the second housing part of the vacuum cleaner when the vacuum cleaner is not in use but when the vacuum cleaner is in use a pressure differential generated by an underpressure located in front of the dual filter arrangement urges the periphery of the radially outwardly extending resilient portion into engagement with the second housing part to form a seal therewith. Since the seal is not in frictional engagement with the second housing part when the second housing part is removed it provides for easier removal of that second housing part.

10
15

The second housing part referred to may comprise the wall of a removable nose cone of the vacuum cleaner through which dust and debris are sucked into the vacuum cleaner.

20

The seal element may be made of any resilient sealing material, such as rubber, neoprene, silicones or other suitable elastomers.

Conveniently, the seal element may be moulded around the periphery of the rim of the pre-filter.

25

In a preferred embodiment of the present invention the pre-filter is releasably latched to a first housing portion of a vacuum cleaner by a latching arrangement against a biasing force generated by the seal element. Preferably, at least one cam surface is located between co-operating latching parts of the latching arrangement, such that the movement of at least one of the latching parts over the cam surface during the unlatching movement causes the seal element to be compressed beyond the degree of

30

compression of the seal element when the pre-filter is latched to the first housing portion. Thus, the seal element has the dual function of providing sealing and of providing resilient biasing of the latching arrangement, thus providing a potential reduction of component parts.

5

In a preferred embodiment at least one keyhole shaped aperture is provided in the rim of the pre-filter through which can be releasably latched a co-operating latch element which extends from the first housing portion. The or each latch element may comprise a peg with an enlarged head which can fit within the widened portion of the aperture and a stem which can fit within the narrow portion of the aperture. In this preferred embodiment the cam surface may surround the aperture and may comprises at least one ridge over which the co-operating latch element must ride when moving into or out of the latched position.

15 Preferably, the primary filter has a peripheral rim via which it is releasably latched between the pre-filter and the first housing portion.

The first housing portion of the vacuum cleaner referred to above may be a housing portion which surrounds an inlet to a fan of the vacuum cleaner.

20

According to a second aspect of the present invention there is provided a concertina filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner, comprising a frame and a concertina shaped arrangement of filter material wherein the concertina shape of the filter material is supported in and maintained by the frame, preferably along opposing zig-zag edges of the filter material. The concertina filter may have the preferred features of the concertina shaped primary filter arrangement described above. Such a concertina filter can be made of relatively inexpensive and flexible fine filter material because the concertina shape is supported by the frame and not by the filter material itself.

30

The present invention will now be described by way of example only with reference to the following Figures in which:

Figure 1 shows a longitudinal cross-section of a hand held battery powered vacuum comprising a dual filter system according to the present invention.

5 Figure 2 shows a front perspective view of a primary filter used in the dual filter system of the vacuum cleaner of Figure 1.

Figure 3 shows a rear perspective view of the primary filter shown in Figure 2.

Figure 4 shows a side view of the primary filter shown in Figures 2 and 3.

10 Figure 5 shows a side perspective view of a pre-filter used in the dual filter system of the vacuum cleaner of Figure 1.

Figure 6 shows a bottom view of the pre-filter shown in Figure 5.

Figure 7 shows a top view of the pre-filter shown in Figures 5 and 6 and shows an array of filter holes provided in the front surface of the pre-filter.

15 Figure 8 shows a longitudinal cross-section of the pre-filter shown in Figures 5 to 7.

Figure 9 shows a side view of the pre-filter shown in Figures 5 to 8 and shows an array of filter holes provided in all the side surfaces of the pre-filter.

Figure 10 shows an enlarged longitudinal cross-section of a portion of the rim of the pre-filter shown in Figures 5 to 9 and its associated seal element.

20 Figure 11 shows a side perspective view of a portion of the upper surface of a rim of an embodiment of a pre-filter similar to that shown in figures 5 to 10.

Figure 12 shows a longitudinal cross-section of a portion the nose cone of the vacuum cleaner shown in Figure 1 and an embodiment of a seal element for the rim of the pre-filter shown in Figures 5 to 11.

25 Figure 13 shows a longitudinal cross-section of a portion the nose cone of the vacuum cleaner similar to that shown in Figure 1 and an embodiment of a seal element for the rim of the pre-filter shown in Figures 5 to 11.

30 The battery powered hand held vacuum cleaner shown in Figure 1 comprises a main housing portion (2) and a nose cone (4) and can be releasably mounted on a charging unit (6) in a known manner. The charging unit (6) can optionally be mounted on a wall for storage and re-charging of the vacuum cleaner.

According to a third aspect of the present invention there is provided filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner in which the filter has a peripheral rim via which it is fitted to a first housing part of a vacuum cleaner, wherein a peripheral seal
5 element made of a resilient material surrounds said rim. Preferably, the seal element comprises a first rearwardly extending resilient portion which extends around the periphery of the rim of the filter towards the first housing part to form a seal therewith when the filter arrangement is fitted to a vacuum cleaner. The seal element may additionally or alternatively have a radially outwardly extending resilient portion
10 according to any preferred embodiment described above in relation to the seal element of the first aspect of the present invention.

According to a fourth aspect of the present invention there is provided a filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an
15 airflow passing through the vacuum cleaner in which the filter has a seal element made of a resilient material for sealing against a housing part of a vacuum cleaner wherein the filter can be releasably latched to a housing portion of a vacuum cleaner by a latching arrangement against a biasing force generated by the seal element. The fourth aspect of the present invention has the same preferred features and advantages
20 as described above in relation to the latch arrangement for the pre-filter of the first aspect of the present invention.

According to further aspects of the present invention there is provided a vacuum cleaner comprising any one of the filter arrangements described above according to
25 the first, second, third or fourth aspects of the present invention. In a preferred form the vacuum cleaner may comprise a first housing portion which houses a battery pack, a motor and a fan and a second housing portion which comprises a nose cone, wherein the battery pack powers the motor which rotatingly drives the fan to generate an airflow which enters the vacuum cleaner through the nose cone and passes through the
30 dual filter arrangement into the fan.

The main housing portion (2) comprises a handle (8) and houses a motor (10) which is powered by a re-chargeable battery unit (12) also housed within the main housing portion. When the vacuum cleaner is mounted on the charging unit (6) the battery unit (12) is electrically connected to the charging unit to charge the battery unit. For this purpose the charging unit (6) can be connected to a mains electricity supply via an electrical cable (14). The motor (10) is switched on and off by movement of an actuator (16) which is slideably mounted on the main housing portion (2). The actuator (16) operates a switch unit (18) which switches the motor (10) on and off.

10 The motor (10) rotatingly drives a fan (20). When the fan (20) is rotated by the motor (10) it draws air into it axially from the front of the fan through an inlet (84) provided in the front of the main housing portion (2), as indicated by arrows (A). The fan (20) expels air radially, as indicated by arrows (B). The air expelled by the fan (20) exits the main housing portion (2) via vents (not shown) provided in said housing portion.

15 A dual filter system (34) which comprises a pre-filter (36) and a primary filter (38) is releasably latched onto the front of the main housing portion (2) in front of the inlet (84) to the fan (20) by a pair of pegs (40) which extend from the front of the main housing portion. The pegs (40) have enlarged heads and can be releasably latched within a corresponding pair of keyhole shaped apertures provided in the pre-filter (36) and in the primary filter (38) in a manner described in more detail below.

20

The nose cone (4) can be releasably fitted onto the main housing portion (2) by the engagement of detent members (22,24) provided on the main housing portion with co-operating recesses (26,28) provided in the nose cone. Detent member (24) can be retracted from recess (28) by depressing a release lever (30) against the force of a biasing spring (32) in order to remove the nose cone (4) from the main housing portion (2). The nose cone (4) comprises an inlet tube (42) for the ingress of dust and debris to be collected by the vacuum cleaner. At the rear end of the inlet tube (42) is provided a deflector (44) for deflecting dust and debris downwardly into a collecting chamber (46) provided in the nose cone (4).

25

30

In use when the vacuum cleaner is detached from the charging unit (6) and the motor (10) is switched on, the impeller (12) rotates to draw an airflow into the front end (48) of the inlet tube (42), along the inlet tube (42) through the dual filter system (34) and axially into the fan (20). The front end (48) of the inlet tube is directed by a user towards a surface from which dust and/or other debris is to be collected. The airflow generated by the fan (20) entrains dust and debris within it and so this dust and debris is pulled up the inlet tube (42) and a proportion of is deflected downwardly with the airflow by the deflector (36) towards collecting chamber (46). In this way some of the dust and debris entrained in the airflow will be removed from the airflow and collected within the collecting chamber (46). The remainder of the dust and debris entrained within the airflow will be separated from the airflow by the dual filter system (34). The proportion of dust and debris separated from the airflow by the pre-filter (36) will drop downwardly, due to gravity, and will be collected in the collecting chamber (46). The remaining, relatively small, proportion of the dust and debris separated from the airflow by the primary filter (38) will be collected in the space between the pre-filter (36) and the primary filter (38).

When a user has collected a pre-determined amount of dust and debris or has completed a debris collecting task, the motor (10) will be switched off and the nose cone (4) removed from the main housing portion (2) by depressing the release lever (30). The dust and debris contained in the collecting chamber (46) can then be disposed of. Also the dual filter system (36) can be removed as required by the operator from the main housing portion (2) and any dust or debris collected on or between the pre-filter (36) and the primary filter (38) can be removed. The dual filter system (34) and nose cone (4) can then be re-fitted onto the main housing portion (2) and the vacuum cleaner is ready for further use or can be stored away for subsequent use.

One of the benefits of the arrangement utilising a dual filter attached to the main housing portion (2) is that this design provides for relative ease of emptying and cleaning the vacuum cleaner. In particular, the user may hold the housing unit in one hand whilst removing the collecting chamber (26) with an opposed hand, the dust and

debris being primarily retained within the collecting chamber (46) and thus can be emptied at the operator's convenience. No additional step is required to remove the pre- or primary filters from the main housing and any debris collected between the primary filter and the pre-filter can simply be removed by vibrating or shaking the
5 housing unit with the filters attached thereto. This enables a continuous operation to empty the vacuum cleaner.

The dual filter system (36) will now be described in more detail, with reference to Figures 1 to 13.

10

The primary filter (38) of the dual filter system (34) shown in Figure 1 comprises a moulded plastic frame within which is supported a concertina of woven polyester filter material (50). The moulded plastic frame comprises a rim (52) from which extend two opposing side support frames (54, 56). Each side support frame (54, 56)
15 comprises an outer frame (60a, 60b, 60c) within which are formed an array of lower forked support arms (58a) and an array of upper forked support arms (58b) which co-operate in a zig-zag formation. The concertina of filter material (50) is supported between the zig-zag formation of opposing support arms (58a, 58b) and by the end support arms (60a, 60c) of the outer frame. In addition triangular shaped sections of
20 woven polyester filter material (62) are supported between adjacent support arms (58a), adjacent support arms (58b), adjacent support arms (60a, 58a) and adjacent support arms (60c, 58a). The triangular sections of filter material (62) provide a side filter surface across the area contained within the outer frame (60a, 60b, 60c) of each support frame (54, 56).

25

The primary filter (38) is manufactured by folding a concertina of filter material (50) within and locating triangular sections of filter material (62) appropriately within a moulding die and then injecting plastics material into the moulding die to form the moulded plastics frame comprising rim (52) and opposing support frames (54, 56).
30 The opposing support frames will thus support the woven filter material (50, 62) securely in position. The folding of the filter material (50) in the concertina

arrangement and the additional triangular sections of filter material (62) provides a primary filter (38) with a relatively large cross-sectional area.

5 The rim (52) of the primary filter (38) has formed within it on opposing sides keyhole shaped apertures (64,66), which are used to releasably latch the primary filter (38) to co-operating pegs (40) provided on the front of the main housing portion (2) of the vacuum cleaner of Figure 1.

10 As shown in Figure 1, in use the primary filter (38) will be surrounded by a pre-filter (36) shown in Figures 5 to 9. The pre-filter (36) comprises a moulded plastic open box-shaped casing having front surface (66) and four side surfaces (68a to 68d) and a rim (70). A resilient seal element (72) extends around the periphery of the rim (70). The front surface (66) and the four side surfaces each have formed through them an array (74) of circular filter holes, for example the array of filter holes (74a) formed in
15 the front surface (66) as shown in Figure 7 and the array of filter holes (74b) formed in the side surface (68b) as shown in Figure 9. Each of the holes in the arrays of holes (74) has a diameter of approximately 1mm although the size may vary, if required between 0.75mm and 1.75mm. The arrays of holes in the pre-filter (36) provide a first coarse filtering stage in front of the primary filter which provides a second fine
20 filtering stage.

To aid in the injection moulding of the pre-filter (36) the front face (66) of the pre-filter comprises a solid circular region (76) from which extend radially outwardly six solid arms (78). The solid circular region (76) and arms (78) assist in the flow of
25 molten plastics material during the injection moulding process, which flow would otherwise be impaired by narrow channels between the holes forming the arrays of holes (74). The solid circular region (76) also provides a region of the pre-filter (36) that can prominently display information such as trade marks.

30 It has been found in practice that the 1mm diameter size of the holes in the pre-filter (36) is generally greater than the majority of the particles of dust and debris entering the nose cone (4) in use of the vacuum cleaner shown in Figure 1. However, the pre-

filter (36) still deflects the majority of particles of dust and debris, irrespective of their size, out of the airflow drawn through the pre-filter (36) by the fan (20). These deflected particles of dust and debris are collected in the collecting chamber (46) of the nose cone (4). Up to 90% of particles of debris and dust normally picked up during household vacuuming and entrained in the airflow in front of the pre-filter (36) can be removed from that airflow by the pre-filter. However, the amount of particulate removed from the airflow is dependent on the size of that particulate.

The 1mm diameter circular hole size used in the pre-filter would be expected not to deflect the generally much smaller sized particles of dust and debris entrained in an airflow through it. However, when the particles of dust and debris entrained within the airflow hit the front surface of the pre-filter (36) the momentum of the particles is reduced or eliminated. The airflow into the pre-filter (36) is often insufficient to then recapture such particles and these particles fall into the collecting chamber (46). This significantly reduces the volume of particles of dust and debris which reach the primary filter (38) and so there is a significant reduction in the amount of blocking of the pores of the filter material used therein by conglomerations of such particles. Furthermore, as the particles that reach the primary filter (38) will have passed through the 1mm diameter holes in the pre-filter (36) they will be of more uniform diameter than if the pre-filter was not used. It has been found that this increased level of uniformity of diameter of particles incident on the filter material (50, 62) of the primary filter (36) is more resistant to binding and thus tends to reduce further the blocking up of the pores in the primary filter by conglomerations of particles. This is because particles of similar diameter are less likely to bind together to form a conglomerated mass that could block the filter material than particles of dissimilar diameters. The more uniform diameter particles that have passed through the pre-filter (36) tend not to bind and instead fall away from the filter material (50, 62) into the space between the pre-filter (36) and the primary filter (38). This reduction of blocking of the pores of the primary filter improves the suction of the vacuum cleaner during use as the airflow to the fan (20) is not impeded by a blocked primary filter (38).

In a similar way to the primary filter (38), the rim (70) of the pre-filter (36) has formed within it on opposing sides keyhole shaped apertures (80, 82), which are used to releasably latch the pre-filter (38) to co-operating pegs (40) provided on the front of the main housing portion (2) of the vacuum cleaner of Figure 1. When the primary
5 filter (38) is received within the pre-filter (36), the keyhole shaped apertures (64, 80) and (66, 82) line up so that the dual filter system (34) comprising the pre-filter (36) and the primary filter (38) can be releasably latched to the main housing portion (2) as a single assembly.

10 To fit the dual filter system (34) to the main housing portion (2), the widened portions of the keyhole shaped apertures (64, 80) and (66, 82) are fitted over the enlarged head of a corresponding one of the pair of pegs (40). The dual filter system (34) is then rotated slightly to slide the stem of the pegs (40) into the narrow portion of the
15 respective keyhole shaped apertures (64, 80) and (66, 82) in order to securely latch the dual filter system (34) to the main housing portion (2) over the inlet (84) to the fan (20). One of the pegs (40) comprising an enlarged head (86) and a stem (88) is shown clearly in dotted lines in Figure 10.

Figure 10 shows in more detail the resilient seal element (72) which surrounds the rim
20 (70) of the pre-filter (36). The seal element (72) is made of a resilient material such as rubber, silicone, neoprene or other suitable elastomers and is intended to form an air tight seal between the pre-filter (36) and the primary filter (48), between the dual filter system (34) and the nose cone (4) and between the dual filter system and the
25 main housing portion (2).

The rim (70) has a stepped portion (90) which extends around its periphery and the resilient seal element (72) is moulded over this stepped portion. The seal element (72) comprises a radially outwardly extending portion (92), which as seen in Figure 1
30 engages the inner surface of the wall of the nose cone (4), when the nose cone is fitted to the main housing portion (2), to form an airtight seal between the dual filter system (34) and the nose cone. The seal element also comprises a first axially rearwardly extending portion (94) (Figure 10) which extends around the periphery of the rim (52)

of the primary filter (38) to engage a forward surface of the main housing portion (2) to form an airtight seal between the dual filter system (34) and the main housing portion, and as a consequence an airtight seal is also formed between the pre-filter (36) and the primary filter (38). The seal element (72) further comprises a second
5 axially rearwardly extending portion (96) against which the rim (52) of the primary filter (38) abuts when the pre-filter (36) and primary filter (38) are together fitted onto the main housing portion. This provides further air tight sealing between the pre-filter (36) and primary filter (38). This sealing is further enhanced by extending the seal element (72) at the keyhole shaped apertures (80,82) so that an extension (98) (See
10 also Figure 6) of the seal element extends around each keyhole shaped aperture (80, 82) partly within a recess (100) formed in the lower side of the rim (70) around said apertures.

Thus, when the dual filter arrangement (34) is assembled and fitted onto the main
15 housing portion (2) the primary filter (38) is inserted into the pre-filter (38) such that the concertina of filter material (50) is received within the box-shaped cavity of the pre-filter, the keyhole shaped apertures (64, 80) and (66, 82) are aligned, the second axially extending portion (96) of the seal (72) abuts the rim (52) of the primary filter (38) and the first axially extending portion (94) of the seal (72) extends around the
20 periphery of the rim (52) of the primary filter (38). The dual filter arrangement is then latched onto the studs (40) provided on the main housing portion (2). This latching of the dual filter system (34) to the pegs (40) presses the rims (52, 70) of the filters together and so reinforces the seal between the pre-filter (36) and primary filter (38) provided by the portion (96) of the seal element (72). It also presses the rim (70) of
25 the pre-filter (36) towards the front surface of the main housing portion (2) and so reinforces the seal between the pre-filter and the main housing portion provided by the portion (94) of the seal element (72).

An alternative design of pre-filter (38) which provides an improved releasable latch
30 connection between the dual filter system (34) and the main housing unit (2) of the vacuum cleaner of Figure 1 is shown in Figure 11. In the arrangement of Figure 11, a raised cam surface (102) is provided on the upper surface of the rim (70) of the pre-

filter (38) bordering the narrow portion and part of the widened portion of each keyhole shaped aperture (80, 82). Each cam surface (102) comprises a pair of ramps (104) facing towards the widened end of the aperture it borders and an opposing pair of ramps (106) facing towards the narrow end of the aperture it borders. Each cam surface (102) co-operates with the underside of the enlarged head portion (86) of a
5 respective peg (40). When the dual filter system (34) is fitted over the pair of pegs (40) provided on the main housing portion (2), the enlarged head portion (86) passes through the widened portion of the respective key shaped apertures (64, 80) and (66, 82). Then the dual filter system (34) is rotated by a small amount so that the neck
10 portion of each peg (40) slides into the narrow portion of the respective apertures and the enlarged head portion (86) of each peg latches the dual filter system into the main housing portion.

With the improved arrangement shown in Figure 11, rotation of the dual filter system
15 (34) in this way, causes the underside of the enlarged head (86) of each peg to ride up the pair of ramps (104) on the respective cam surface (102). This urges the rim (70) of the pre-filter (36) towards the main housing portion (2) and thus towards the rim (52) of the primary filter (38) against the biasing force of the axially extending portions (94, 96) of the seal element (72). Further rotation of the dual filter system
20 causes the underside of the enlarged head (84) of each peg to move down the opposing ramps (106) and come to rest in its final latched position against the flat raised portion of the cam surface (102) surrounding the narrowed portion of each aperture (80, 82). This slightly releases the compression of the axially extending portions (94, 96) of the seal element (72). However, with the dual filter system in its
25 latched position, the rim (70) of the pre-filter system is urged sufficiently towards the main housing portion (2) and towards the rim (52) of the primary filter (36) for the axially extending portions (94, 96) to form an air tight seal against the main housing portion and the rim (52) respectively. This ensures that in use of the vacuum cleaner all airflow to the fan (20) passes through the pre-filter (36) and through the primary
30 filter (38). Furthermore, the two ridges (108) on each cam surface (102) between the opposing ramps (104, 106) serve as a retaining means to retain the pegs (40) in their latched position against the resilience of the axially extending portions (94, 96) of the

sealing element (72). In this way the dual filter system can only be unlatched from the pegs (40) by rotation in a direction opposite to that required to latch the dual filter system to the pegs, which rotation can only occur if a force is applied which is sufficient to compress the axially extending portions (94, 96) so that the underside of the enlarged heads (86) of the pegs (40) can ride over the ridges (108) in the cam surfaces (102).

Alternatively, or in conjunction with the use of the cam surfaces (102), internal ribs may be provided around the interior surface of the collecting chamber (46) so as the collecting chamber (46) is moved into engagement with the main housing portion (2), these ribs engage with the rim (70) of the pre-filter system so as to serve to compress the axially extending portions (94, 96) of the sealed element (72) into respective engagement with the housing portion (2) and primary filter (36) accordingly. The use of ribs in this manner will provide a uniformly distributed compression force about the entire periphery of the seal of the pre-filter.

Figure 13 shows a cross-section of the seal element (72) shown in Figure 10, with like parts identified by like numerals. Figure 13 also shows a modified portion of the outer wall of the nose cone (4) adjacent the seal element (72) from that shown in Figure 1. In the Figure 13 embodiment an internal raised wall (110) extends around the portion of the internal surface of the nose cone (4) which surrounds the seal element (72). This creates an improved air tight seal between the dual filter system (34) and the inner surface of the nose cone (4). The radially extending portion (92) of the resilient seal element (72) abuts the rear surface of the wall (110). In use of the vacuum cleaner the underpressure created in the forward part (112) of the nose cone (4) relative to the ambient air pressure in the region (114) in front of the main housing portion (2) reinforces a sealing engagement between the portion (92) of the sealing element (72) and the wall (110). The pressure differential urges the front surface of the resilient radially extending portion (92) of the seal element (72) into sealing engagement with the rear surface of the wall (110). Again this ensures that all the airflow through the nose cone (4) passes through the dual filter arrangement (34) into the fan (20).

Figure 12 shows an alternative embodiment to that shown in Figure 13, with like parts identified by like numerals, in which the wall (110) is not required on the internal surface of the nose cone (4) and the radially extending portion (92) of the seal element (72) is bent rearwardly to form a third axially rearwardly extending portion (116).

- 5 In Figure 12 the radially extending portion (92) is bent rearwardly through approximately 90° . Thus, as shown in solid lines in Figure 12, when the nose cone (4) is fitted on the main housing unit (2) with the vacuum cleaner switched off, there is no sealing engagement between the seal element (72) and the nose cone (4). However, when the vacuum cleaner is switched on the pressure differential between the
- 10 underpressure created in the region (112) of the nose cone (4) and the ambient pressure in the region (114) causes the third resilient axially extending portion (116) to move outwardly into the position showed in Figure 12 in dotted lines and into a sealing engagement with the internal surface of the wall of the nose cone (4). Thus, when the vacuum is in use a seal is provided between the dual filter system (34) and
- 15 the nose cone (4) to ensure that all the airflow through the nose cone passes through the dual filter system. However, when the vacuum cleaner is not in use the lack of engagement between the seal element (72) and the nose cone (4) can help to prevent wear of the portion (116) of the seal element due to the repeated removal and replacement of the nose cone (4) during the lifetime of the vacuum cleaner.

CLAIMS

1. A dual filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner, comprising;

5

a coarse pre-filter,

a fine primary filter which is located rearwardly of the pre-filter in the direction of flow of the airflow.

10

2. A dual filter arrangement according to claim 1 wherein the diameter of the pores of the pre-filter is set at a substantially uniform value.

3. A dual filter arrangement according to claim 2 wherein the diameter of the pores of the pre-filter is set at one substantially uniform value within the range 0.75mm to 1.75mm.

15

4. A dual filter arrangement according to claim 3 wherein the diameter of the pores of the pre-filter is set at a substantially uniform value of 1mm.

20

5. A dual filter arrangement according to any one of the preceding claims wherein the primary filter comprises a concertina shaped arrangement of a fine filter material.

6. A dual filter arrangement according to claim 5 wherein the primary filter comprises a frame and the concertina shaped arrangement of a fine filter material and the concertina shape of the filter material is supported in and maintained by the frame.

25

7. A dual filter arrangement according to claim 5 or claim 6 wherein the filter material is supported by the frame along opposing corrugated edges.

30

8. A dual filter arrangement according to any one of claims 5 to 7 wherein the primary filter comprises a frame including two opposing arrays of arms and the

concertina shaped arrangement of fine filter material is supported between opposing pairs of said arms.

9. A dual filter arrangement according to claim 8 wherein said opposing arrays of arms are each arranged to form a zig-zag formation.

10. A dual filter arrangement according to claim 8 or claim 9 wherein additional areas of fine filter material are located between adjacent arms of the arrays of arms.

11. A dual filter arrangement according to any one of claims 6 to 10 wherein the frame of the primary filter comprises a moulded plastics material.

12. A dual filter arrangement according to any one of the preceding claims wherein the pre-filter is formed with a recess within which the primary filter is received.

13. A dual filter arrangement according to any one of the preceding claims wherein the pre-filter comprises an open boxed-shaped structure in which the array of pores is located in at least one of the sides of the structure.

14. A dual filter arrangement according to claim 13 wherein the array of pores is located in all five sides of the structure.

15. A dual filter arrangement according to any one of the preceding claims wherein the pre-filter is made from a moulded plastics material.

16. A dual filter arrangement according to any one of the preceding claims in which the pre-filter has a peripheral rim via which it is fitted to the primary filter and/or to a housing part of a vacuum cleaner, wherein a peripheral seal element made of a resilient material surrounds said rim.

17. A dual filter arrangement according to claim 16 wherein said seal element comprises a first rearwardly extending resilient portion which extends around the

periphery of the rim of the pre-filter towards the primary filter and which surrounds the periphery of the primary filter when the dual filter arrangement is fitted to a vacuum cleaner.

- 5 18. A dual filter arrangement according to claim 17 wherein the first rearwardly extending resilient portion extends rearwardly beyond the primary filter to engage a portion of a first housing part of a vacuum cleaner to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner.
- 10 19. A dual filter arrangement according to any one of claims 16 to 18 wherein said seal element comprises a second rearwardly extending resilient portion which extends around the periphery of the rim of the pre-filter towards the primary filter to engage a peripheral rim of the primary filter to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner.
- 15 20. A dual filter arrangement according to any one of claims 16 to 19 in which said seal element comprises a substantially radially outwardly extending resilient portion which extends around the periphery of the rim of the pre-filter to engage a second housing part of a vacuum cleaner to form a seal therewith when the dual filter arrangement is fitted to a vacuum cleaner.
- 20 21. A dual filter arrangement according to claim 20 wherein a radially inwardly extending wall is provided on the second housing part of the vacuum cleaner and a front facing surface of the radially outwardly extending resilient portion engages a rearwardly facing surface of said wall to form a seal therebetween.
- 25 22. A dual filter arrangement according to claim 21 wherein in use of the vacuum cleaner the seal between the radially outwardly extending resilient portion and the radially inwardly extending wall is reinforced by a pressure differential generated by an underpressure located in front of the dual filter arrangement.
- 30

23. A dual filter arrangement according to claim 16 to 22 in which said sealing element comprises a substantially radially outwardly extending resilient portion which extends around the periphery of the rim of the pre-filter wherein the periphery of the radially outwardly extending resilient portion is arranged such that it does not engage the second housing part of the vacuum cleaner when the vacuum cleaner is not in use but when the vacuum cleaner is in use a pressure differential generated by an underpressure located in front of the dual filter arrangement urges the periphery of the radially outwardly extending resilient portion into engagement with the second housing part to form a seal therewith.

24. A dual filter arrangement according to any one of claims 20 to 23 wherein said second housing part comprises the wall of a removable nose cone of the vacuum cleaner through which dust and debris are sucked into the vacuum cleaner.

25. A dual filter arrangement according to any one of claims 16 to 24 wherein the seal element is made of rubber or elastomer.

26. A dual filter arrangement according to any one of claims 16 to 25 wherein the seal element is moulded around the periphery of the rim of the pre-filter.

27. A dual filter arrangement according to any one of claims 16 to 26 wherein the pre-filter is releasably latched to a first housing portion of a vacuum cleaner by a latching arrangement against a biasing force generated by the seal element.

28. A dual filter arrangement according to claim 27 wherein at least one cam surface is located between co-operating latching parts of the latching arrangement, such that the movement of at least one of the latching parts over the cam surface during the latching or unlatching movement causes the seal element to be compressed beyond the degree of compression of the seal element when the pre-filter is latched to the first housing portion.

29. A dual filter arrangement according to claim 27 or claim 28 wherein at least one keyhole shaped aperture is provided in the rim of the pre-filter through which can be releasably latched a co-operating latch element which extends from the first housing portion.

5

30. A dual filter arrangement according to claim 29 wherein the or each latch element comprises a peg with an enlarged head which can fit within the widened portion of the aperture and a stem which can fit within the narrow portion of the aperture.

10

31. A dual filter arrangement according to claim 29 or claim 30 wherein the cam surface surrounds the aperture and comprises at least one ridge over which the co-operating latch element must ride when moving into or out of the latched position.

15 32. A dual filter arrangement according to any one of claims 27 to 31 wherein the primary filter has a peripheral rim via which it is releasably latched between the pre-filter and the first housing portion.

20 33. A dual filter arrangement according to any one of claims 18 to 32 wherein the first housing portion of the vacuum cleaner is a housing portion which surrounds an inlet to a fan of the vacuum cleaner.

25 34. A dual filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner substantially as hereinbefore described with reference to any one of the accompanying Figures.

35. A vacuum cleaner comprising a dual filter arrangement according to any one of claims 1 to 34.

30 36. A battery powered hand held vacuum cleaner according to claim 35 comprising a first housing portion which houses a battery pack, a motor and a fan and a second housing portion which comprises a nose cone, wherein the battery pack powers the

motor which rotatingly drives the fan to generate an airflow which enters the vacuum cleaner through the nose cone and passes through the dual filter arrangement into the fan.

5 37. A concertina filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner, comprising a frame and a concertina shaped arrangement of filter material wherein the concertina shape of the filter material is supported in and maintained by the frame.

10 38. A concertina filter arrangement according to claim 37 wherein the frame supports the filter material along its opposed zig-zag edges.

39. A concertina filter arrangement according to claim 37 or claim 38 wherein the frame comprises opposing arrays of arms and the filter material is supported between
15 opposing pairs of said arms.

40. A concertina filter arrangement according to claim 39 wherein said opposing arrays of arms are each arranged to form a zig-zag formation.

20 41. A concertina filter arrangement according to claim 39 or claim 40 wherein additional pieces of fine filter material are located between adjacent arms of the arrays of arms.

42. A concertina filter arrangement according to any one of claims 37 to 41 wherein
25 the frame additionally comprises a peripheral rim via which it can be releasably fitted to a housing portion of a vacuum cleaner.

43. A concertina filter arrangement according to any one of claims 37 to 42 wherein the frame of the filter comprises a moulded plastics material.

30

44. A concertina filter arrangement substantially as hereinbefore described with particular reference to any one of Figures 1 to 4.

45. A filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner in which the filter has a peripheral rim via which it is fitted to a first housing part of a vacuum cleaner, wherein an annular seal element made of a resilient material surrounds said rim.

5

46. A filter arrangement according to claim 45 wherein said seal element comprises a first rearwardly extending resilient portion which extends around the periphery of the rim of the filter towards the first housing part to form a seal therewith when the filter arrangement is fitted to a vacuum cleaner.

10

47. A filter arrangement according to claim 45 or 46 in which the seal element comprises a substantially radially outwardly extending resilient portion which extends around the periphery of the rim of the filter to engage a second housing part of the vacuum cleaner to form a seal therewith when the filter arrangement is fitted to the vacuum cleaner.

15

48. A dual filter arrangement according to claim 47 wherein a radially inwardly extending wall is provided on the second housing part of the vacuum cleaner and a front facing surface of the radially outwardly extending resilient portion engages a rearwardly facing surface of said wall to form a seal therebetween.

20

49. A filter arrangement according to claim 48 wherein in use of the vacuum cleaner the seal between the radially outwardly extending resilient portion and the radially inwardly extending wall is reinforced by a pressure differential generated by an underpressure located in front of the filter arrangement.

25

50. A filter arrangement according to claim 45 or 46 in which the seal element comprises a substantially radially outwardly extending portion which extends around the periphery of the rim of the filter, wherein the periphery of the radially outwardly extending resilient portion is arranged such that it does not engage the second housing part of the vacuum cleaner when the vacuum cleaner is not in use but when the vacuum cleaner is in use a pressure differential generated by an underpressure located

30

in front of the filter arrangement urges the periphery of the radially outwardly extending resilient portion into engagement with the second housing part to form a seal therebetween.

5 51. A filter arrangement according to any one of claims 47 to 50 wherein said second housing part comprises the wall of a removable nose cone of the vacuum cleaner through which dust and debris are sucked into the vacuum cleaner.

10 52. A filter arrangement according to any one of claims 45 to 51 wherein the seal element is made of rubber or an elastomer material.

53. A filter arrangement according to any one of claims 45 to 52 wherein the seal element is moulded around the periphery of the rim of the pre-filter.

15 54. A filter arrangement having a seal element substantially as hereinbefore described with particular reference to Figures 5 to 13.

20 55. A filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner in which the filter has a seal element made of a resilient material for sealing against a housing part of a vacuum cleaner wherein the filter can be releasably latched to a housing portion of a vacuum cleaner by a latching arrangement against a biasing force generated by the seal element.

25 56. A filter arrangement according to claim 55 wherein at least one cam surface is located between co-operating latching parts of the latching arrangement, such that the movement of at least one of the latching parts over the cam surface during the latching or unlatching movement causes the seal element to be compressed beyond the degree of compression of the seal element when the filter is latched to the first housing
30 portion.

57. A dual filter arrangement according to claim 55 or claim 56 wherein at least one keyhole shaped aperture is provided in the filter through which can be releasably latched a co-operating latch element which extends from the first housing portion.
- 5 58. A filter arrangement according to claim 57 wherein the or each latch element comprises a peg with an enlarged head which can fit within the widened portion of the aperture and a stem which can fit within the narrow portion of the aperture.
- 10 59. A filter arrangement according to claim 57 or claim 58 wherein the cam surface surrounds the aperture and comprises at least one ridge over which the co-operating latch element must ride when moving into or out of the latched position.
- 15 60. A filter arrangement according to any one of claims 55 to 59 wherein the housing portion of the vacuum cleaner is a housing portion which surrounds an inlet to the vacuum cleaner fan.
61. A filter arrangement according to any one of claims 55 to 60 wherein the seal element is a seal element as set out in claims 45 to 53.
- 20 62. A filter arrangement with a latching arrangement substantially as hereinbefore described with particular reference to Figure 11.

ABSTRACT**Improvements in Vacuum Cleaners**

- 5 A dual filter arrangement for a vacuum cleaner for filtering particles of dust and debris from an airflow passing through the vacuum cleaner, comprising a coarse pre-filter having an array of pores formed therein of substantially uniform diameter and a fine primary filter which is located rearwardly of the pre-filter in the direction of flow of the airflow.

10

Figure 1.



11/5









FIG. 1.

2/5



13/5



4/5






FIG 9


$$s | s^*$$


FIG. 10




FIG 11





FIG 12 114



f1513

If for some reason, applicant has not submitted a sufficient fee to prevent the abandonment of this application, please charge our Deposit Account No. 02-2548 for any further fees which may be due. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

HARNESS, DICKEY & PIERCE, P.L.C.
Attorney For Applicant



Mark D. Elchuk
Reg. No. 33,686

P.O. Box 828
Bloomfield Hills, MI 48303
(248) 641-1600
November 9, 2000